
CBS 80 Series Shield heights from .800"




80-CBS Series Black = inches Red = mm									
STYLE	FIG.	A HEIGHT		B Pin spacing		C Standoffs		D Pin Length	
80-CBS surface mount	1	.80	(20,3)	none none		one	none		
81-CBS	7	.80	(20,3)	1.0	(25,4)	.05	(1,27)	.12	(3,05)
82-CBS	5	.80	(20,3)	1.0	(25,4)	none		.12	(3,05)
82NH	6	.80	(20,3)	1.0	(25,4)	none		.12	(3,05)
83-CBS	4	.80	(20,3)	.50	(12,7)	.05	(1,27)	.12	(3,05)
83A-CBS	4	.80	(20,3)	.50	(12,7)	.05	(1,27)	.06	(1,53)
84-CBS	2	.80	(20,3)	.50	(12,7)	none		.12	(3,05)
84NH	3	.80	(20,3)	.50	(12,7)	none		.12	(3,05)
84VH	9	.80	(20,3)	.50	(12,7)	none		.12	(3,05)
85-CBS	7	.80	(20,3)	1.0	(25,4)	.01	(,250)	.12	(3,05)
86-CBS	7	.80	(20,3)	1.0	(25,4)	.05	(1,27)	.15	(3,81)
87-CBS	7	.80	(20,3)	1.0	(25,4)	.01	(,250)	.15	(3,81)
88-CBS	2	.80	(20,3)	.50	(12,7)	none		.15	(3,81)
89-CBS	8	.80	(20,3)	.25	(6,35)	none		.12	(3,05)

NOTES

- Drawings in figures 1-8 are not to scale; see chart for sizing
- Standard cover height .280" (7,11) 80-CBS
- Other cover heights available, consult factory










K CBS 80 Series






AVAILABLE HEIGHTS: 80 SERIES - .80" TO 2.0" (20,3 TO 50,5) Recommended hole size: .050" (1,27)








Pin pattern viewed from top of shield. Consult factory for pin patterns for your application

.25" Pin Pattern









































DIMPLES AVAILABLE UPON REQUEST



.250' TYP

80 Series Specs

Sizes: .50" x .50" to 12" x 24" (.25" increments) Shapes: Squares, rectangles and odd shapes in .25" increments

Heights: .80" to 4.00"

Mounting Pins: .25", .50" or 1.00" spacing Surface Mount: Available for all 80 series CBS **Std Material:** .015" (,38) pre-tin plated steel **Cover Retention:** 1.5 - 2.5 lb./linear inch Shielding Effectiveness: up to 60 dB


Standard Options

- Formed fence and cover unassembled (F)
- Assembled fence and cover (A)
- Flat fence and formed cover (U)
- Pre-tin plated Phos Bronze (P), Alloy 770 (N)
- Ventilation holes (SV 15% or DV 30%)
- Dimples for improved retention (D)

Ordering a CBS is Easy

- Select your style number "81-CBS"
- 2. Choose standard options listed above -"81-CBSFNSV"
- 3. Specify your width in .25" increments from .50" to 12.00" - "81-CBSFNSV-2.5"
- Specify your length in .25" increments from .50" to 24.00" - "81-CBSFNSV-2.5x4.5"
- 5. Specify your height from board to inside cover from .80" to 2.00" "81-CBSFNSV-2.5x4.5x.80"

.50" Pin Pattern



The Leading Edge in EMI Shielding Technology